

RUST-OLEUM®
INDUSTRIAL



PRE-PAINT CLEANER

Concentrated pre-paint cleaner for most surfaces

- Multi-surface cleaner for walls, window/door frames, floors and metals
- No further rinsing is needed after wiping the surface; saves time
- Effortlessly removes all organic and inorganic pollution
- Makes the surface anti-static to prevent adhesion of dust prior to painting
- Non-foaming, biodegradable formulation



KNOW-HOW TO PROTECT™

WWW.RUST-OLEUM.EU

PRE-PAINT CLEANER

DESCRIPTION

Effective, concentrated biodegradable cleaner to quickly clean all types of surfaces prior to painting.

RECOMMENDED USE

Pre-paint Cleaner for all types of surfaces: floors, walls, doors, window frames, metal, windows, door frames, etc. Cleans, degreases and also removes nicotine stains. Makes the surface anti-static to prevent adhesion of dust prior to painting. Does not foam.

TECHNICAL DATA

Density: 1.05 kg/l

DRYING TIMES AT 20°C/RH 50%

THEORETICAL CONSUMPTION

Ca. 100 m²/l at a dilution of 1 : 20

PRACTICAL CONSUMPTION

Practical coverage depends on many factors such as porosity, roughness of the substrate, contamination level and dilution during application.

DIRECTIONS FOR USE

Shake well before use. Scrape off grease, oil, dirt and other pollution as much as possible. Dilute RUST-OLEUM® Pre-paint cleaner to the required mixture and apply on the surface. Rub with a brush or white nylon pad and allow to work in for several minutes if necessary. Then wipe thoroughly with a damp sponge or cloth. With stubborn soiling repeat the treatment or leave to work in longer, possibly with a higher concentration.

APPLICATION CONDITIONS

Temperature of air, substrate and material between 5 and 35°C.

REMARKS

Because of its concentrated composition, Pre-Paint Cleaner is very economical in use. Depending on the degree of contamination, the product should be diluted in a ratio of between 1:10 and 1:100.

1 : 10 ovens, motors, extremely dirty floors

1 : 20 kitchens, machines, gas stoves, garden furniture

1 : 50 paintwork, nicotine stains

1 : 100 windows, mirrors, sun-beds etc.

SAFETY DATA

pH: 11.30

VOC level: 0 g/l

Flashpoint: Not flammable

Remarks regarding safety: Consult Safety Data Sheet and Safety Information printed on the can.

SHELF LIFE

2 years from date of production in unopened cans, if stored in dry, well ventilated areas, not in direct sunlight at temperatures between 5° and 40°C.

Date issued: 08/12/2016

Available colours & pack sizes: Please refer to the respective product page on www.rust-oleum.eu for an overview of actual available colours and pack sizes.

Disclaimer: The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. The user will be deemed to have satisfied him/herself independently as to the suitability of our products for his/her own particular purpose. In no event shall Rust-Oleum Europe be liable for consequential or incidental damages. Products must be stored, handled, and applied under conditions complying with Rust-Oleum Europe recommendations detailed within the latest copy of the product data sheet. It is the users responsibility to ensure that they have the current copy. Latest copies of the product data sheet is available for free and downloadable from www.rust-oleum.eu or upon a request to our Customer Services department. Rust-Oleum Europe reserves the right to change the properties of its' products without prior notification.

Rust-Oleum Netherlands B.V.
Postbus 138
4700 AC Roosendaal
The Netherlands
T : +31 (0) 165 593 636
F : +31 (0) 165 593 600
info@rust-oleum.eu

Rust-Oleum UK Ltd.
PO Box 261
Chester-le-Street
DH3 9EH United Kingdom
T : +44 (0)2476 717 329
F : +44 (0)2476 718 930
info@rust-oleum.eu

Rust-Oleum France S.A.S.
11, rue Jules Verne - B.P. 60039
95322 St-Leu-La-Forêt Cedex
France
T : +33(0) 130 40 00 44
F : +33(0) 130 40 99 80
info@rust-oleum.eu

N.V. Martin Mathys S.A.
Kolenbergstraat 23
3545 Zelem
Belgium
T : +32 (0) 13 460 200
F : +32 (0) 13 460 201
info@rust-oleum.eu