

Commercial Solutions Division

3M™ Safety-Walk™ Resilient Fine anti-slip surfacing

220

280

Product Description

3M™ Safety-Walk™ Resilient Fine anti-slip surfacing 220 transparent and 3M™ Safety-Walk™ Resilient Fine anti-slip surfacing 280 white consist of a fine textured resilient top surface. The reverse side is coated with an acrylic pressure sensitive adhesive covered by a removable liner. The products provide a smooth, durable, slip resistant surface for wet area applications. Safety-Walk Resilient Fine anti-slip surfacing 220 and 280 is designed for use as an anti-slip material for bare foot traffic and wet areas. The product is ideal for shower rooms, baths, changing rooms, around saunas, but also for applications on diving boards, boats, water skis.

Product Line	Safety-Walk	220	transparent
		280	white

Sizes Safety-Walk Resilient Fine anti-slip surfacing is available in different roll widths and in different pre-cut treads. Please contact your local 3M contact for further information.

Accessories	3M Primer	3M Safety-Walk Edge Sealer
	- 3M™ Tape Primer 83 - 3M™ Primer 94 - rubber hand roller	- 3M™ Edge Sealing Compound 1103

Product Characteristics

These are indicative values for unprocessed products.
Contact your 3M representative for a custom specification.

Physical & Application	Property and Test Method	Value / Result
	Thickness (without liner)	0.51 mm
	Weight (without liner)	640 g/m²
	Resistance to UV	good
	Fire behaviour	Classification
	EN 13501-1: 2010	Bfl s1
	EU Building and Construction	
	Slip Resistance	Classification
	DIN 51130: 02.2010	R = 11 / V (μ = > 0.34 - 0.51)
	For wetloaded barefoot areas DIN 51097	A
	Minimum Application Temperature	+10°C
	Service Temperature	-10°C to +66°C

The values above are the results of illustrative lab test measurements and shall not be considered as a commitment from 3M.

Chemical Resistance	Water	R	R = Recommended for non continuous immersion I = Recommended for intermittent exposure only NR = Not recommended IC = Can stand incidental contact, if thorough weekly cleaning/rinsing
	Soap (1% Ivory Flakes in water)	R	
	Detergent (1% Dreft in water)	R	
	Bleach (5.25% sodium Hypochlorite)	R	
	1% Sodium Hydroxide	R	
	1% Hydrochloric Acid	R	
	25% Sulfuric acid in water	R	
	Isopropyl Alcohol (25%)	I	
	Methyl Ethyl Ketone	NR	
	Mineral Spirits	NR	
	Trichloroethylene	NR	
	Peanut Oil	R	
	Hydraulic Fluid (Skydrol 500B)	NR	
	Motor Oil	R	
	Gasoline (unleaded)	NR	
	Diesel fuel	NR	
	50% Anti-freeze in water	R	
	Wind screen washer fluid	R	
	Salt Water	R	
Storage	Shelf life	5 years from the date on the original box	
	Storage conditions!	+4°C to +38°C, out of sunlight, original container in clean area, humidity: 50% - 60%.	
	The shelf life as defined above remains an indicative and maximum data, subject to many external and non-controllable factors. It may never be interpreted as warranty.		
Disposal	Post-consumer waste can be disposed of in appropriate containers and/or be incinerated. European code for waste disposal: 20.01.04		
Origin	Made in USA		
	Converted in France.		
Source of Supply	France		

Durability The product is designed to be used in light traffic areas under bare foot traffic only. Shoe or wheeled traffic will significantly reduce product life.

Surface Preparation Make sure surface is clean, dry, smooth and above minimum temperature of application.
Repair or replace any damaged or broken surface.
Remove chipped, cracked or peeled paint from surface.
Strip waxed floors prior to washing.
Use appropriate cleaner or solvent wipe to clean surface.

Type of surface	Recommended preparation
Bare metal, polyethylene, polypropylene	Solvent wipe
Painted metal, painted plastics, painted wood, gel-coated fiberglass, epoxy floors	Solvent wipe or degrease wash, rinse and let dry
Porous concrete	Degrease wash, rinse and let dry
Painted concrete	Degrease wash, rinse and let dry
Vinyl tile, marble, terrazzo, ceramic	Strip off floor finish, wash, rinse and let dry
Quarry tile	Degrease wash, rinse and let dry

Application

Tools needed:
rubber hand roller or rubber mallet

1. Individual pieces should be spaced a minimum of 12 mm apart and a maximum of 50 mm apart.
2. Round the corners of any pieces cut from rolls.
3. Peel protective liner back about 50 mm from one end and position piece on surface.
Note: minimize touching (contaminating) adhesive with fingers.
4. Continue to remove liner and press firmly in place as liner is removed.
5. For small pieces, peel liner off piece. Holding piece by its edges, curve it gently with the adhesive side out. Align the middle of the piece over the middle of the target surface and press down.
6. Finally press into firm contact with surface using a rubber hand roller by starting in middle and rolling out towards edges.
7. On steps, apply 3M Safety-Walk materials 12 to 15 mm from stair edge to prevent edge curl and premature wear.

Helpful hints for proper application

Wet areas:

For extra protection from excessive moisture or liquids (not constant moisture) use 3M Edge Sealer to protect the edges of 3M Safety-Walk materials against penetration of liquids.

Priming

1. Properly clean the floor following “surface preparation” procedure.
2. Use a paint brush and paint on a thin coat of primer where the 3M Safety-Walk 280 materials are to be applied.
3. Allow the primed area to dry thoroughly (no evidence of stickiness or tackiness) before applying 3M Safety-Walk material.

Maintenance

Periodically inspect product application to maintain product effectiveness.

Keep free of dirt and other residue that might impair functionality.

General purpose treads should be decked-brushed regularly.

Use appropriate degreaser/cleaner as a general maintenance cleaner to keep material and surrounding surfaces free of soil and grease.

Removal and Replacement

To remove and replace worn or torn material:

Start by pulling up old material. Use of a heat gun and a scraper will assist in this process.

After total removal of old materials, use a degreaser or solvent based cleaner to remove adhesive residues before proceeding with re-application of 3M Safety-Walk materials.

Remarks

This bulletin provides technical information only.

Important notice

All questions of warranty and liability relating to this product are governed by the terms and conditions of the sale, subject, where applicable, to the prevailing law.

Before using, the user must determine the suitability of the product for its required or intended use, and the user assumes all risk and liability whatsoever in connection therewith.

Additional information

Visit the web site of your local subsidiary at www.3M.eu/facilities.com for getting:

- a complete product overview about materials 3M is offering



Commercial Solutions Division
Hermeslaan 7
1831 Diegem, Belgium

Responsible for this technical bulletin

3M Deutschland GmbH
Carl-Schurz-Str. 1
41453 Neuss, Germany

3M and Safety-Walk are trademarks of 3M Company. All other trademarks are the property of their respective owners.

The use of trademark signs and brand names in this bulletin is based upon US standards. These standards may vary from country to country outside the USA.